

45°F

CAUTIONS CONTAINS

SHERWIN-WILLIAMS 702465
912-638-0022

05/28/20

Order # 0156261

Application.

Wood Prime
Superior Oil-Base

LIENCE
IN

ARCHITECTURAL
ACRYLIC

COROB MODULA HF

coat of the app
d surfaces requi
5°F, substrates n
ure the air, surfac
F and at least 5°F a
ow is expected in
surface temperatu
On large expanses
terial temperatures

OMP(B011) 670 GULF STREAM

CUSTOM SHER-COLOR MATCH

*COLORANT

-White

-Blue

-3-Deep Gold

0Z	32	64	128
-	59	1	1
-	26	1	-
-	9	1	1

/polyester brush
- 3/4" nap synt
essure: 2000

this coating
w on the surfac
ology allows yo
s concern abou

QUART
K43W00053

Handwritten signature

DEEP
640413571

NOT RECOMMENDED FOR USE ON VINYL

For
water. Do not p
and recycling.

on surface, peel
the store where
change or return

CAUTION: Returnable Tinted Col
always To
the j... ent to
of the... to
mixed... containers

ventria

eye wa-

zziness,

ear re-

SH ap-

. Avoid

. Wash

ontainer

Do not

er con-

ST AID:

t, flush

amounts

ention if

allowed,

er, hos-

or physi-

chemicals

california

with de-

ve harm.

RNALLY.

EACH OF
24 (1/10)

Ingredients
Water
37-39
Titanium
(1314-50-2)